

DATA CAPTURE AND STORAGE

Go-Between™**Standard Features**

- LED onboard for testing data transmission
- Captures data and stores it on a USB flash drive (up to 8 GB not included)
- Transfer data to your PC using the USB flash drive
- Text file examples (actual text will be dependent on transmitted file)
- 02:50PM
11/13/2012
GROSS 58 lb
- 02:50PM
11/13/2012
GROSS 68 lb

Specifications**Power:**

Requires 5 VDC

Baud Rate:

9600

Data Bits:

8

Parity:

None

Customer Supplied:

Power and USB flash drive

Industrial Enclosure Option:7.5 × 7.5 × 4.5 in
(19 × 19 × 12 cm)
Latch for lock**Warranty:**

One-year limited

Part Number/Price

| Part # | Description | Price |
|--------|---|---------|
| 153265 | go-between board, requires 5 volts | Consult |
| 153266 | go-between industrial enclosure, requires 5 volts | Consult |
| 153267 | go-between desk enclosure, power supply included | Consult |

Options/Accessories

| Part # | Description | Price |
|--------|---|------------|
| 154797 | Adapter, power 5 VDC 2A 90 to 264 VAC, U.S. plug, cULus | Consult |
| 195607 | USB flash drive, 8 GB | Consult |
| 130789 | Null modem DB9 adapter female to male | Consult |
| 119064 | Null modem adapter, DB9 F/F | Consult |
| 50764 | Straight cable, DB9 F/F | Consult |
| 66535 | Null modem DB9 F/F | Consult |
| 22436 | DB9 cable to blunt end | Consult |
| 15493 | Cable four-conductor | Consult/ft |

