

## HIGH CAPACITY

**GX-M Series****Standard Features**

- Internal calibration
- Auto environmental compensation
- IP65/NEMA Type 4
- RS-232 interface for connecting to printer or PC
- Data memory function
- Quick reference operation card
- Time and date
- Vacuum Fluorescent Display (VFD)
- Underhook weighing

**Specifications****Weighing Units:**

Pound, Carat, Pennyweight, Troy Ounce, Grain,  
Decimal Ounce, Pound/Ounce

**Operating Modes:**

Counting, Percentage

**Power:**

120 /240 V AC adapter

**Stabilization time:**

Approx. 1.5 seconds

**Sensitivity Drift (10 °C to 30 °C / 50 °F to 86 °F):**

GX-8202M: ±2 ppm/°C

GX-8202MD: ±3 ppm/°C

GX-10202M: ±2 ppm/°C

GX-12001M, GX-22001M, GX-32001M: ±3 ppm/°C

GX-32001MD: ±5 ppm/°C

**Calibration Weight:**

GX-8202M/MD: 2 kg to 8 kg

GX-10202M: 2 kg to 10 kg

GX-12001M: 5 kg, 10 kg

GX-22001M: 5 kg, 10 kg, 20 kg

GX-32001M/MD: 5 kg, 10 kg, 20 kg, 30 kg

**Operating Temperature:**

41 °F to 104 °F (-5 °C to 40 °C)

**Est. Weight:**

18.3 lb (8.3 kg)

**Warranty:**

Five-year limited

**Return Policy:**

A&D Weighing standard policy -  
restock fee may apply

Model	Capacity	Readability	Repeatability	Linearity	Pan Size	Dimensions	Part #	List Price
<b>GX-8202M</b>	8.2 kg	0.01 g	0.01 g	±0.03 g	10.62 × 8.26 in (270 × 210 mm)	11.81 × 13.98 × 4.37 in (300 × 355 × 111 mm)	<b>207408</b>	Consult
<b>GX-8202MD</b>	2.2 kg / 8.2 kg	0.01 g / 0.1 g	0.01 g / 0.05 g	±0.02 g / ±0.1 g	10.62 × 8.26 in (270 × 210 mm)	11.81 × 13.98 × 4.37 in (300 × 355 × 111 mm)	<b>207409</b>	Consult
<b>GX-10202M</b>	10.2 kg	0.01 g	0.01 g	±0.03 g	10.62 × 8.26 in (270 × 210 mm)	11.81 × 13.98 × 4.37 in (300 × 355 × 111 mm)	<b>207410</b>	Consult
<b>GX-12001M</b>	12.2 kg	0.1 g	0.1 g	±0.2 g	10.62 × 8.26 in (270 × 210 mm)	11.81 × 13.98 × 4.37 in (300 × 355 × 111 mm)	<b>207411</b>	Consult
<b>GX-22001M</b>	22.2 kg	0.1 g	0.1 g	±0.2 g	10.62 × 8.26 in (270 × 210 mm)	11.81 × 13.98 × 4.37 in (300 × 355 × 111 mm)	<b>207412</b>	Consult
<b>GX-32001M</b>	32.2 kg	0.1 g	0.1 g	±0.2 g	10.62 × 8.26 in (270 × 210 mm)	11.81 × 13.98 × 4.37 in (300 × 355 × 111 mm)	<b>207413</b>	Consult
<b>GX-32001MD</b>	6.2 kg / 32.2 kg	0.1 g/1 g	0.1 g / 0.5 g	±0.2 g / ±1 g	10.62 × 8.26 in (270 × 210 mm)	11.81 × 13.98 × 4.37 in (300 × 355 × 111 mm)	<b>207414</b>	Consult

**Options/Accessories**

Part#	A&D Model#	Description	Price
<b>207431</b>	GX-04K*	Comparator/output and RS-232C/20 mA interface	Consult
<b>207432</b>	GX-06K*	Analog output/20 mA interface	Consult
<b>97784</b>	GX-07K**	Waterproof cable for standard RS-232C	Consult
<b>102899</b>	GXX-12	Animal weighing pan	Consult
<b>102898</b>	GXX-31	Draft shield	Consult
<b>97605</b>	AD-100-2	Anti-theft device	Consult
<b>97785</b>	AX:073007197A	Protective in-use cover	Consult
<b>97649</b>	TB:648	AC adapter (120 V/220 V)	Consult
<b>151247</b>	AD-1688	Data logger	Consult
<b>196128</b>	AD-8127	Impact dot matrix, statistical printer, includes cable	Consult

\*GX-04K, GX-06K, replace standard RS-232C and cannot be used at the same time.

IP65 rating does not apply when the GX-04K or the GX-06K is installed.

\*\*Use the GX-07K optional waterproof RS-232C cable, in order to use the standard RS-232 interface for water and dust proof (IP65).

