

LEGAL FOR TRADE

VALOR[®] 7000 Series

Standard Features

- Touchless sensors
- Backlit dual LCD display
- Illuminated up-front level indicator
- Internal rechargeable battery
- ABS plastic housing
- Skid-resistant leveling feet
- Menu lock switch
- Multiple application modes
- RS-232 interface for connecting to printer or PC
- Fast stabilizing time

Specifications

Weighing Units

Pound, Ounce, Kilogram, Gram

Operating Modes

Weighing, Percent, Checkweighing, Accumulation

Power

100-240 V, internal rechargeable battery 210-hour operation with 12-hour full charge

Stabilization Time

≤ 1 second

NTEP Resolution

V71P1502T: 3 lb x 0.001 lb

V71P3T: 6 lb x 0.002 lb

V71P6T: 15 lb x 0.005 lb

V71P15T: 30 lb x 0.01 lb

V71P30T: 60 lb x 0.02 lb

Operating Temperature

14° F to 104° F (-10° C to 40° C)

Calibration Weight

1502T: 1.5kg / 3lb

3T: 3kg / 6lb

6T: 6kg / 15lb

15T: 15kg / 30lb

30T: 30kg / 60lb

Est. Weight

9.2 lb (4.2 kg)

Warranty

One-year limited warranty

Return Policy

OHAUS Standard Policy - restock fee may apply

Approvals

NTEP: CC 13-022

Measurement Canada: AM-5907C

OIML: R76/2006-NL1-12-46

NSF



Model	Capacity	Readability	Pan Size	Dimensions	Part #	List Price
V71P1502T	1.5 kg	0.00005 kg	11.8 x 8.9 in (300 x 225 mm)	12.2 x 12.9 x 4.6 in (311 x 327 x 117 mm)	157316	Consult
V71P3T	3 kg	0.0001 kg	11.8 x 8.9 in (300 x 225 mm)	12.2 x 12.9 x 4.6 in (311 x 327 x 117 mm)	157317	Consult
V71P6T	6 kg	0.0002 kg	11.8 x 8.9 in (300 x 225 mm)	12.2 x 12.9 x 4.6 in (311 x 327 x 117 mm)	157318	Consult
V71P15T	15 kg	0.0005 kg	11.8 x 8.9 in (300 x 225 mm)	12.2 x 12.9 x 4.6 in (311 x 327 x 117 mm)	157319	Consult
V71P30T	30 kg	0.001 kg	11.8 x 8.9 in (300 x 225 mm)	12.2 x 12.9 x 4.6 in (311 x 327 x 117 mm)	157320	Consult

Options/Accessories

Part #	Model #	Description	Price
154638	30037447	Ethernet kit	Consult

