



Picture is a representation of actual product.

Approvals



Order Information


Load Rating	Part #	Est. Weight	Price
250 kg	31254	2 lb	Consult
500 kg	31255	2 lb	Consult
1,000 kg	31256	2 lb	Consult
2,500 kg	31257	3 lb	Consult

Dimensions

Rated Capacity	A	B	C	D	E
kg/mm					
250 to 1,000	M12 × 1.75-6H	25.4	19.1	50.8	76.0
2,500	M20 × 1.5-6H	31.8	25.4	76.2	108.0

Specifications

- Full Scale Output:**
3.0 mV/V ±0.25%
- Bridge Resistance:**
350 ohm, nominal
- Material/Finish:**
Alloy steel
- Temperature:**
Operating range
0 °F to 150 °F (-18 °C to 65 °C)
- Seal Type:**
Environmentally sealed, IP67
- Safe Overload:**
150% full scale
- Rated Excitation:**
5 to 10 VAC/DC (15V maximum)
- Combined Error:**
0.02% full scale
- Insulation Resistance:**
5,000 megohm
- Cable Length:**
6 m
- Cable Diameter:**
0.200 in polyurethane jacket
- Cable Color Code:**
Red +Excitation
Black -Excitation
Green +Signal
White -Signal
- Warranty:**
Two-year limited
- Approvals:**
cFMus
OIML R60/1991-GB-95-09



**RICE LAKE
LOAD CELLS**