



# EL146, 4 Wire

Standard Load Cell Cable



Approvals



## Standard Features

### EL146 Standard Cable

- Four-wire load cell cable
- 20 AWG tinned copper wire stranded for flexibility
- Braided shielding is encased in red PVC
- All conductors are industry-standard color coded
- Diameter: 0.25 in
- Use the four-wire cable for repairing or extending existing cable
- Temperature rating: -22 °F to 126 °F (-30 °C to 80 °C)



## Part Number/Price

Part #	Continuous Roll	Description	Price
15505	100 ft	Four-conductor cable	Consult
15506	250 ft	Four-conductor cable	Consult
15507	500 ft	Four-conductor cable	Consult
15508	1,000 ft	Four-conductor cable	Consult
15493	Custom length	Four-conductor cable	Consult/ft

HARDWARE AND ACCESSORIES

# EL146HE, 4 Wire

Hostile Environment Load Cell Cable



## Standard Features

### EL146HE Hostile Environment Cable

- Designed for use in hostile environments
- Polyurethane jacketing provides superior chemical and abrasion resistance
- RFI and EMI protected with foil overbraid shield
- Unmatched durability, yet extremely flexible
- All conductors are industry-standard color coded
- Diameter: 0.32 in
- Temperature rating: -22 °F to 176 °F (-30 °C to 80 °C)
- 500 V rating

## Part Number/Price

Part #	Continuous Roll	Description	Price
15510	100 ft	Four-conductor hostile environment cable	Consult
15511	250 ft	Four-conductor hostile environment cable	Consult
15512	500 ft	Four-conductor hostile environment cable	Consult
15513	1,000 ft	Four-conductor hostile environment cable	Consult
15494	Custom Length	Four-conductor hostile environment cable	Consult/ft