## **EZ Mount 1 with Painted RL72020P**

Rice Lake Weighing Systems



### **Order Information**

Load Rating (Per Module)	Part#	Price							
Single Module (Does NOT Include Load Cell)									
5,000 lb to 20,000 lb	17943	Consult							
30,000 lb to 60,000 lb	17944	Consult							
100,000 lb	17945	Consult							
150,000 lb	29011	Consult							
3-Module Kit									
5,000 lb	208957	Consult							
10,000 lb	208959	Consult							
20,000 lb	208961	Consult							
30,000 lb	208963	Consult							
40,000 lb	208965	Consult							
50,000 lb	208967	Consult							
60,000 lb	208969	Consult							
100,000 lb	208971	Consult							
150,000 lb	208973	Consult							

Load Rating (Per Module)	Part#	Price
4-Module Kit		
5,000 lb	208958	Consult
10,000 lb	208960	Consult
20,000 lb	208962	Consult
30,000 lb	208964	Consult
40,000 lb	208966	Consult
50,000 lb	208968	Consult
60,000 lb	208970	Consult
100,000 lb	208972	Consult
150,000 lb	208974	Consult
Dummy Load Cells	(Mild Steel)	
5,000 lb to 20,000 lb	33749	Consult
30,000 lb to 60,000 lb	74016	Consult
100,000 lb	94175	Consult
150,000 lb	158715	Consult
Grounding Kit		
5,000 lb-60,000 lb	126419	Consult

Includes ground strap and mounting hardware per mount

#### Complete Kit Includes

- One JB4SS NEMA Type 4X stainless steel signal trim junction box
- Three or four EZ Mount 1 stainless steel compression mounts
- Three or four RL72020P alloy painted double-ended shear beam load cells
- 25 ft of hostile environment EL147HE SURVIVOR load cell cable

#### **Standard Features**

- Capacities (per module): 5,000 to 150,000 lb
- Unique sliding pin design compensates for thermal expansion/contraction
- · Self-checking
- · Easy load cell replacement
- Simplified design allows bolting directly to tank
- Center-loaded double-ended shear beam design
- · Low-profile design
- 304 stainless steel construction (mount)

#### **Applications**

• Medium- to heavy-capacity tank and fertilizer hopper weighing applications

# EZ Mount 1 with Painted RL72020P

Rice Lake Weighing Systems

#### **Dimensions**

Rated Capacity	С	C1	Н	H1	H2	L	L1	L2	L3	L4	T	W	W1	W2	W3
lb/in															
5,000 to 20,000	0.56	1.06	5.31	0.75	0.50	11.00	8.00	3.00	6.00	6.87	5/8-18 UNF	7.50	4.00	3.00	6.00
30,000 to 60,000	0.68	1.19	8.43	1.00	0.75	15.00	11.50	5.12	8.00	8.50	1-14 UNS	10.00	6.00	5.12	8.00
100,000 to 150,000	0.81	1.38	10.37	1.25	1.25	18.00	14.00	7.50	10.00	9.50	1-14 UNS	12.00	9.00	7.50	10.00



