RoughDeck® PW-1 Mild Steel Low-profile Pallet Weighing Floor Scale



Approvals

C FM US

FLOOR SCALES


Part Number/Price

| Part # | Size (W × L × H) | Capacity | Est. Weight | Price |
|--------|----------------------|----------|-------------|---------|
| 177904 | 48 in × 48 in × 3 in | 2,500 lb | 200 lb | Consult |
| 177905 | 48 in × 60 in × 3 in | 2,500 lb | 210 lb | Consult |
| 177906 | 60 in × 60 in × 3 in | 2,500 lb | 235 lb | Consult |
| 177907 | 48 in × 48 in × 3 in | 5,000 lb | 200 lb | Consult |
| 177908 | 48 in × 60 in × 3 in | 5,000 lb | 210 lb | Consult |
| 177909 | 60 in × 60 in × 3 in | 5,000 lb | 235 lb | Consult |

Options/Accessories

| Part # | Description | Price |
|---------|--|---------|
| 18777 | Floor anchor plates, mild steel (set of 2) | Consult |
| 19352 | Floor stand for indicator, 36.3 in high, mild steel | Consult |
| 126384 | Floor stand for indicator, 48 in high, mild steel | Consult |
| 178250 | Wheel kit option (wheels engage at a 28° angle) | Consult |
| Consult | Mild steel deck with RL32018S IP66 stainless steel cFMus approved load cells and hardware | Consult |
| Consult | Mild steel deck with RL32218S-HE hermetically sealed IP69K stainless steel cFMus approved load cells and hardware | Consult |
| Consult | Epoxy paint | Consult |

| Dimensions | | | |
|--------------------|-------------|--|--|
| 4 × 4 ft (160 lb) | | | |
| А | 48.00 in | | |
| В | 39.63 in | | |
| С | 36.00 in | | |
| D | 48.00 in | | |
| 4×51 | ft (170 lb) | | |
| А | 48.00 in | | |
| В | 39.63 in | | |
| С | 48.00 in | | |
| D | 60.00 in | | |
| 5 × 5 | ft (195 lb) | | |
| Α | 60.00 in | | |
| В | 51.63 in | | |
| С | 48.00 in | | |
| D | 60.00 in | | |
| Note: 1 in=25.4 mm | | | |
| | | | |



Standard Features

- Low-profile design
- 20 ft SURVIVOR® EL147HE hostile environment load cell cable
- Top-access junction box
- Four adjustable stainless steel SUREFOOT™ support feet
- · Four alloy steel, shear beam load cells

Specifications

End Load Capacity: 80% full scale at 2,500 lb 100% full scale at 5,000 lb

Cable Length:

20 ft (6.1 m) for connecting junction box to indicator

Junction Box:

TuffSeal® JB4SS stainless steel, NEMA Type 4X junction box with signal trim card

Welding:

Stitch, consult factory if continuous is required

Warranty (limited):

Load cells: Two-year All other components: One-year