29

Ranger 5 Variable Range Simulator

Specifications

Fixed Steps:

-0.5 mV/V-4.5 mV/V range

Vernier:

Variable range: up to 0.5 mV/V, up to 1 mV/V, up to 1.5 mV/V

Impedance: 350 ohm nominal

Nonlinearity: Less than 0.02%

Connectors: Binding posts suitable for bangn

Binding posts suitable for banana plug or 14 gauge wire

Temperature Coefficient: ± 5 ppm/°C

Dimensions:

(L x W x H) 4.5 in x 3.5 in x 1.25 in

Warranty:

One-year limited warranty



Standard Features

- ABS plastic case, weighs less than 1 lb
- Fixed rotary switch, -0.5 mV/V to 4.5 mV/V in nine steps of 0.5 mV/V per step
- 10-turn vernier knob with locking graduated dial
- Vernier selection of four ranges: Off, fine, medium and coarse
- Ideal tool for calibrating indicator A/D offset and gain setting
- A/D calibration steps for -0.5 mV/V for offset and 4.5 mV/V for gain
- Used in testing, troubleshooting and calibrating digital weight indicators
- Binding posts are color coded to ISA S37.8 standard

Part Number/Price

Part #	Description	Price
68031	Ranger 5 simulator	Consult

Options/Accessories

Part #	Description	Price
21116	Cable with banana plugs	Consult

Ranger 7 Variable Range Simulator

Specifications

Vernier:

Two ranges; one is equal to the sum of the 0.05 mV/V switch and the 0 mV/V-0.5 mV/V switch. The other is the sum of the 0.5 mV/V, 0.1 mV/V and 0.01 mV/V switches.

Load Impedance:

Three settings: X0.5= 700 ohms X1= 350 ohms (one standard load cell) X4= 87.5 ohms (four load cell platform)

Linearity:

± 0.01% + 1æV

Connectors:

Low Thermal Electronics, Type 2758 precision gold plated binding posts Standard banana jacks or 14 AWG wire

Temperature Coefficient:

5 ppm/°C Zero Offset:

± 0.0005 mV/V

Output Range:

0 mV/V-3 mV/V in 0.01 mV/V steps

LED Annunciators:

EXC + EXC -Offset ON 0.5 mV/V 0.1 mV/V



Standard Features

- Designed for high resolution
- Used in high precision testing, troubleshooting and calibrating digital weight indicators
- Switchable offset
- Painted die-cast enclosure

Part Number/Price

Part#	Description	Price
157323	Ranger 7 high resolution calibration simulator	Consult

Options/Accessories

Part # Description

21116	Cable with	banana	plugs

An ISO 9001 Registered Company © 2021/2022 Rice Lake Weighing Systems 11/21 Prices and specifications subject to change without notice. Visit ricelake.com for current prices

Price 429

		-
Came		14
COUR	ш	н.