



Approvals



Part Number/Price

| NTEP Approved Part # | Measurement Canada Approved Part # | Size (W × L × H) | Capacity | Est. Weight | Price |
|----------------------|------------------------------------|--------------------------|----------------------|-------------|---------|
| 18680 [†] | 193293 | 2.5 ft × 2.5 ft × 3.5 in | 2,000 lb (1,000 kg) | 173 lb | Consult |
| 18681 [†] | 193294 | 3 ft × 3 ft × 3.5 in | 2,000 lb (1,000 kg) | 232 lb | Consult |
| 18682 | 193296 | 4 ft × 4 ft × 3.5 in | 5,000 lb (2,500 kg) | 375 lb | Consult |
| 18683 | 193297 | 4 ft × 4 ft × 3.5 in | 10,000 lb (5,000 kg) | 490 lb | Consult |
| 18684 | 193298 | 4 ft × 5 ft × 3.5 in | 5,000 lb (2,500 kg) | 437 lb | Consult |
| 18685 | 193307 | 4 ft × 5 ft × 3.5 in | 10,000 lb (5,000 kg) | 567 lb | Consult |
| 18688 | 193308 | 5 ft × 5 ft × 3.5 in | 5,000 lb (2,500 kg) | 541 lb | Consult |
| 18689 | 193309 | 5 ft × 5 ft × 3.5 in | 10,000 lb (5,000 kg) | 696 lb | Consult |
| 18692 | 193310 | 5 ft × 7 ft × 3.5 in | 5,000 lb (2,500 kg) | 734 lb | Consult |
| 18693 | 193311 | 5 ft × 7 ft × 3.5 in | 10,000 lb (5,000 kg) | 929 lb | Consult |

[†]Not recommended for use with pallet jacks

Options/Accessories

| Part # | Description | Price |
|---------|---|---|
| Consult | Access ramps available | See catalog page 386 |
| Consult | Pit frames available | See catalog page 389 |
| Consult | Bumper guards available | See catalog page 392 through catalog page 394 |
| Consult | Portability frames available | See catalog page 395 through catalog page 400 |
| 18778 | Floor anchor plates, stainless steel (set of two) | Consult |
| Consult | Four drilled deck holes for scale height adjustment | Consult |
| 28740 | Floor stand for indicator, 36.3 in high, stainless steel | Consult |
| Consult | Stainless steel diamond treadplate safety deck | Consult |
| Consult | Forklift channel option (up to 5 × 7 ft, 10,000 lb, accommodates fork tines no larger than (W × H) 5 × 2 in, fork entry is on opposite side of junction box location) | Consult |

Standard Features

- Rugged washdown design
- 304 stainless steel construction
- Rigid 304 stainless steel channel frame
- Four stainless steel, hermetically sealed, IP69K shear beam load cells
- 20 ft of SURVIVOR® EL147HE hostile environment load cell cable
- Load cells protected on all four sides
- Smooth stainless steel deck

Specifications

End Load Capacity:

- 100% full scale at 2,000 lb and 5,000 lb
- 80% full scale at 10,000 lb

Cable Length:

20 ft (6.1 m)

Scale Weldment:

AISI304L, glass bead blasted for even appearance

Junction Box:

TuffSeal® JB4SS stainless steel, NEMA Type 4X junction box with signal trim card

Welding:

Stitch, consult factory if continuous is required

Threaded Eyebolt:

Hole (1/2-20 NF) located in center of deck for easy lifting

Warranty (limited):

Weldment: Five-year
Load cells: Two-year
All other components: One-year

Approvals:

NTEP Certified, CC 92-001 Class III 5,000 d
Measurement Canada AM-4827, Class III 5,000 d